



Latex



Abrasion



Tear



Puncture

# GL503

Polyester | Latex | Crinkle

ANSI/ISEA 105-2016 – CUT A1 | ABRASION 4 | PUNCTURE 3  
EN388: 2016 – 3142X

Latex crinkle palm coating // 10 gauge polyester liner // Good grip in all conditions

GL503 S – 2XL

### Suggested Applications

Manufacturing // Bottling & Canning // Recycling // Assembly

### Glove Breakdown

Type: Dipped Glove
Material: Latex Crinkle
Liner: 10 Gauge Polyester
Cuff: Polyester + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

### Testing Performance

EN388: 2016 – 3142X

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



Product markings may vary. Refer to the product sheet for the most current test report results.

### Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

### Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China